GreenLife

Ausschreibungstext
GreenLife Flachtank-System 8.000 l - Regenwassererdtank

Volumen: 8.000 l

Mögliche Anschlussgrößen: DN 100
inkl. 2 Ausgleichsdömen 380 mm – 580 mm stufenlos ausziehbar und
bis 5° neigbar zur optimalen Geländeanpassung

Einstiegsöffnung 600 mm
inkl. Sicherheitskunststoffabdeckung 200 kg begehbar,
Kindersicher verschraubbar mit 2 Edelstahlschrauben

Optionen: PKW-befahrbar (bis 600 kg Radlast) – Set für PKW-Befahrbarkeit (G0001724)

im Vergleich zu Beton einfacheres Handling – geringeres Gewicht

Flachtank aus Polyethylen (PE), hergestellt im Rotationssinterverfahren, hohe Formstabilität durch patentiertes Stabilitätsdesign, UV-Beständig und lichtundurchlässig, mit 2 aufgesetzten Ausgleichsdömen DN 600 mm, Domschacht stufenlos einstellbar, 3 Anschlüsse DN 100für Zu- und Überlauf, sowie Versorgungsleitung, weitere Montageflächen an allen Seiten mit diverse Anschlussmöglichkeiten für Retentionsdrossel oder Untenverbindung.

Geeignet zur Lagerung von Regenwasser, häuslichen Abwässern, Betriebswasser.

Optionale Ausstattungsvarianten erhältlich

Ausstattungsversion „Biovitor“:
Der Biovitor- der biologische Regenwasserfilter - perfekt dimensionierte Größenverhältnisse der Kammern und Durchlässe gewährleisten optimale biologische Abläufe mit höchstem Wirkungsgrad.
inklusive Biovitor DN 100 und Überlaufsiphon mit Tierschutz, Ausgleichsdom mit Abdeckung (begehbar, aus Kunststoff), 3 Anschlüssen DN 100

Auch als Retentionsbehälter erhältlich (die Retentionsdrossel ist nicht nachträglich einbaubar!)

15 Jahre Materialgarantie auf den Behälter!
Hohe Formstabilität durch dicke Wandstärken
UV-Beständigkeit für konstante Materialqualität.

Inhalt:	8.000 l
Gewicht:	380 kg
Material:	PE
Länge:	4.400 mm
Breite:	2.420 mm
Höhe mit Dom:	1.240 – 1.440 mm
Artikelnummer:	G0005639
Mengeneinheit:	Stück

Herstellerangaben:

GreenLife GmbH
Sacktannen 1a
19057 Schwerin
Telefon +49 (0) 385 – 77337-0
Telefax +49 (0) 385 – 77337-33
Web www.greenlife.de
E-Mail projects@greenlife.info

Menge: …… Einheit: **Stk**. EP: …… GP: ……

GreenLife

tender specifications
GreenLife flat tank system 8000 l – rainwater underground tank

volume: 8000 l

possible connection sizes: DN 100
incl. 2 sliding domes 380 – 580 mm infinitely extendable and 5° tilt for optimized adaptation to terrain surface

access opening 600 mm (according DIN 1989) – for inspection purposes
incl. plastic safety cover (load capacity: 200 kg, walkable),
child-safe screwed – with 2 stainless steel screws

options: accessible by cars (up to 600 kg wheel load) – Kit accessible by cars (G0001724)

easier handling in comparison to concrete shafts – lower weight

Underground flat tank made of polyethylene (PE), produced in rotation sintering method, high dimensional stability due to patented stability design, UV-resistant and impervious to light, with 2 sliding domes DN 600 mm manhole continuously adjustable, 3 connections DN 100 for supply and overflow, and supply line, additional mounting surfaces on all sides with several interfaces for retention throttle or bottom connection.

Suitable for the storage of rainwater, domestic waste water, process water.

Optional equipment versions available!

version with „Biovitor":
The Biovitor - the biological rainwater filter - perfectly dimensioned chambers and diffusers ensure optimal biological processes with maximum efficiency.
including Biovitor DN 100 and overflow siphon with animal protection, sliding dome with cover (walkable, made of plastic), 3 DN 100 connections.

Even as retention tank available (retention throttle is retrofitted!)

15 years material warranty on the tanks/shafts!
strong walls – best construction of GreenLife stability profiles
UV resistance for a constant material quality

volume:	8000 l
weight:	380 kg
material:	PE
length:	4400 mm
diameter:	2420 mm
height:	1240 – 1440 mm
item no.:	G0005639
unit of quantity:	piece

manufacturer:

GreenLife GmbH
Sacktannen 1a
D-19057 Schwerin
Germany
phone +49 (0) 385 – 77337-0
fax +49 (0) 385 – 77337-33
web www.greenlife.de
e-mail projects@greenlife.info

quantity: ..... unit: **piece** single price: ..... total price: .....