

GreenLife's greywater recycling plants treat lightly contaminated wastewater from personal hygiene (shower, bathtub, hand basin). The entire recycling process consists of sedimentation of the suspended solids, biological treatment and ultrafiltration (MBR membrane bioreactor). The membrane filter technology used ensures complete separation of the biomass from the purified grey water. The clear water is free of solids, bacteria and germs with a guaranteed retention rate of 99.99%.

The result is clear, germ-free service water that is stored in the service water tank and can be used for toilets, washing machines, cleaning purposes, garden irrigation and/or industrial applications. The quality of the service water meets the requirements of the European Bathing Water Directives 76/160/EEC and 2006/7/EC as well as DIN 19650, Class 2.



technical data

typ	
designation	GW1 1.0 – 250
item number	G0001740
production guideline	DIN EN 16941-2, DIN EN 1717
capacity	
filtration capacity	250 l/day
volumen filtration	500 l
volumen service water	500 l
pressure booster system	GAP X120
max. flow rate	100 l/min
max. work pressure	4,5 bar
connections	
mains water back-up (optional, larger possible)	DN13 / 3/4" solenoid drain valve
service water	1 1/4"
inlet greywater	DN75
overflow into the sewage system	DN50 / DN75
electric main supply	
voltage	230 V / 50 Hz
rated power	970 W
rated current	4,4 A
fuse / overload protection	on site
weight, dimensions, color	
empty weight	149 kg
max. total weight in operation	1.149 kg
color of the tanks	light grey
filtration tank	Ø = 650 mm, h = 1.670 mm
service water tank	Ø = 650 mm, h = 1.670 mm