

GreenLife's greywater recycling plants treat lightly contaminated wastewater from personal hygiene (shower, bathtub, hand basin). The entire recycling process consists of sedimentation of the suspended solids, biological treatment and ultrafiltration (MBR membrane bioreactor). The membrane filter technology used ensures complete separation of the biomass from the purified grey water. The clear water is free of solids, bacteria and germs with a guaranteed retention rate of 99.99%.

The result is clear, germ-free service water that is stored in the service water tank and can be used for toilets, washing machines, cleaning purposes, garden irrigation and/or industrial applications. The quality of the service water meets the requirements of the European Bathing Water Directives 76/160/EEC and 2006/7/EC as well as DIN 19650, Class 2.



technical data

typ	
designation	GWI 20.2 – 20.000
item number	G0003905
production guideline	DIN EN 16941-2, DIN EN 1717
capacity	
filtration capacity	20.000 l/day
volumen sedimentation	4.000 l
volumen aeration	16.000 l
volumen filtration	8.350 l
volumen service water	8.000 l
connections	
mains water back-up (optional, larger possible)	DN25 / 1" solenoid drain valve
service water	1 1/4"
inlet greywater	DN160
overflow into the sewage system	DN160
electric main supply	
voltage	230 V / 50 Hz
rated power	3.093 W
rated current	13,5 A
fuse / overload protection	on site
weight, dimensions, color	
empty weight	3.239 kg
max. total weight in operation	39.589 kg
color of the tanks	light grey
sedimentation tank	l = 2.430 mm, b = 1.000 mm, h = 1.975 mm
aeration tank	l = 2.430 mm, b = 1.000 mm, h = 1.975 mm
filtration tank	l = 2.430 mm, b = 1.000 mm, h = 1.975 mm
filtrate shaft	Ø = 550 mm, h = 1.695 mm
service water tank	l = 2.430 mm, b = 1.000 mm, h = 1.975 mm